

ANDARD FOR SAFETY
Low-Voltage Fuses – Part 18: Class CD
Fuses

Ultrophycom. clickto vientre full
Ultrophycom

Copyright Underwriters Laboratories Inc.

ULMORM.COM. Click to view the full POF of UL 248-18 2022

UL Standard for Safety for Low-Voltage Fuses – Part 18: Class CD Fuses, UL 248-18

First Edition, Dated March 31, 2022

Summary of Topics

This is the first edition of of ANSI/UL 248-18, the Standard for Low-Voltage Fuses – Part 18: Class CD Fuses dated March 31, 2022.

As noted in the Commitment for Amendments statement located on the back side of the title page, UL, CSA, and ANCE are committed to updating this harmonized standard jointly.

The requirements are substantially in accordance with Proposal(s) on this subject dated July 9, 2021.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

ULMORM.COM. Click to view the full poor of UL. 248-18 2022



Association of Standardization and Certification NMX-J-009/248/18-2022-ANCE **First Edition**



CSA Group CSA C22.2 No. 248.18:22



Underwriters Laboratories Inc. UL 248-18 **First Edition**

March 31, 2022

March 31, 2022

Citck to view the Citck to view th Low-Voltage Fuses - Part 18: Class CD Fuses

American National Standars ANSI/UL 248-18-2022



Commitment for Amendments

This standard is issued jointly by the Association of Standardization and Certification (ANCE), the Canadian Standards Association (operating as "CSA Group"), and Underwriters Laboratories Inc. (UL). Comments or proposals for revisions on any part of the standard may be submitted to ANCE, CSA Group, or UL at anytime. Revisions to this standard will be made only after processing according to the standards development procedures of ANCE, CSA Group, and UL. CSA Group and UL will issue revisions to this standard by means of a new edition or revised or additional pages bearing their date of issue. ANCE will incorporate the same revisions into a new edition of the standard bearing the same date of issue as the CSA Group and UL pages.

Copyright © 2022 ANCE

Rights reserved in favor of ANCE.

ISBN 978-1-4883-3828-1 © 2022 Canadian Standards Association

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

This Standard is subject to review within five years from the date of publication, and suggestions for its improvement will be referred to the appropriate committee. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line: Standard designation (number); relevant clause, table, and/or figure number; wording of the proposed change; and rationale for the change.

To purchase CSA Group Standards and related publications, visit CSA Group's Online Store at www.csagroup.org/store/ or call toll-free 1-800-463-6727 or 416-747-4044.

Copyright © 2022 Underwriters Laboratories Inc.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

This ANSI/UL Standard for Safety consists of the First edition. The most recent designation of ANSI/UL 248-18 as an American National Standard (ANSI) occurred on March 31, 2022. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page (front and back), or the Preface.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at https://csds.ul.com.

To purchase UL Standards, visit UL's Standards Sales Site at http://www.shopulstandards.com/HowToOrder.aspx or call toll-free 1-888-853-3503.

CONTENTS

Preface		5
		_
1	Scope	
2	Referenced Publications	
3	Units of Measurement	7
4	General	7
5	Classification	7
6	Characteristics	8
	6.1 Voltage rating	8
	6.2 Current rating 6.3 Interrupting rating 6.4 Peak let-through current and clearing I²t characteristics	8
	6.3 Interrupting rating	8
	6.4 Peak let-through current and clearing I ² t characteristics	8
7	Construction	8
8	Tests	10
O	Tests	10
	8.2. Verification of everload eneration	10
	8.2 Verification of overload operation	10
	9.4 Verification of peak let through ourrent and elegring 12t phorasteristics	10
	8.4 Verification of peak let-through current and clearing let characteristics	1
	8.3 Verification of operation at rated voltage	

No Text on This Page

JILNORM. COM. Cick to view the full POF of UL. 248-188 2022

Preface

This is the harmonized ANCE, CSA Group, and UL standard for Low-Voltage Fuses – Part 18: Class CD Fuses, UL 248-18. It is the first edition of NMX-J-009/248/18-ANCE, first edition of CSA C22.2 No. 248.18, and the first edition of UL 248-18.

This harmonized standard was prepared by the Association of Standardization and Certification, (ANCE), CSA Group, and Underwriters Laboratories Inc. (UL). The efforts and support of the Technical Harmonization Subcommittee, 32B, Fuses, Fuseholders, on the Harmonization of Electrotechnical Standards of the Nations of the Americas (CANENA), are gratefully acknowledged.

This Standard is considered suitable for use for conformity assessment within the stated scope of the Standard.

The present Mexican Standard was developed by the TC 32 Fuses from the Comite de Normalizacion de la Asociacion de Normalizacion y Certificacion, A.C., CONANCE, with the collaboration of the fuse manufacturers and users.

This Standard was reviewed by the CSA Subcommittee on Fuses and Fuseholders and approved by the CSA Technical Committee on Industrial Products under the jurisdiction of the CSA Strategic Steering Committee on the Requirements for Electrical Safety. This standard has been developed in compliance with the Standards Council of Canada requirements for National Standards of Canada. It has been published as a National Standard of Canada by CSA Group

Application of the Standard

Where reference is made to a specific number of samples to be tested, the specified number is to be considered a minimum quantity.

Note: Although the intended primary application of this Standard is stated in its Scope, it is important to note that it remains the responsibility of the users of the Standard to judge its suitability for their particular purpose.

Level of Harmonization

This trinational standard is published as an identical standard for ANCE, CSA Group, and UL. An identical standard is a standard that is exactly the same in technical content except for national differences resulting from conflicts in codes and governmental regulations and basic safety principles and requirements. Presentation is word for word except for editorial changes.

Interpretations

The interpretation by the standards development organization of an identical or equivalent standard is based on the literal text to determine compliance with the standard in accordance with the procedural rules of the standards development organization. If more than one interpretation of the literal text has been identified, a revision is to be proposed as soon as possible to each of the standards development organizations to more accurately reflect the intent.

No Text on This Page

JILNORM. COM. Cick to view the full POF of UL. 248-188 2022

Low-Voltage Fuses - Part 18: Class CD Fuses

1 Scope

- 1.1 This Part is intended to be read together with the Standard for Low-Voltage Fuses Part 1: General Requirements, hereafter referred to as Part 1. The titles of the Clauses in this Part correspond to the similarly titled Clauses in Part 1. The requirements of Part 1 apply unless modified by this Part. For the Part 1 requirements, refer to the Standard for Low-Voltage Fuses Part 1: General Requirements, NMX-J-009-248/1-ANCE / CSA C22.2 No. 248.1 / UL 248-1.
- 1.2 This Standard applies to Class CD fuses rated 31 60 A and 600 Vac.

2 Referenced Publications

- 2.1 Any undated reference to a code or standard appearing in the requirements of this Standard shall be interpreted as referring to the latest edition of that code or standard.
- 2.2 When a reference is made to a code or standard, the product shall comply with the code or standard of the country in which the product is intended to be used.
- 2.3 Throughout this Standard, the CSA standard references apply to products intended for use in Canada, the ANCE NMX standard references apply to products intended for use in Mexico, and the UL standard references apply to products intended for use in the United States. Combined references are separated by a slash ("/") to denote the difference between the applicable requirements specified for use in Canada, Mexico, and the United States.
- 2.4 The following publications are referenced in this Standard:

United States	Canada	Mexico
NFPA 70, National Electrical Code	UL 248-1, Low-Voltage Fuses – Part 1: General Requirements (Trinational)	NOM – 001, Mexican Electrical Code
COL	CSA C22.2 No. 0, General Requirements – Canadian Electrical Code, Part II	
UL 248-1, Low-Voltage Fuses Part 1: General Requirements (Trinational)	CSA C22.2 No. 248.1, Low-Voltage Fuses – Part 1: General Requirements (Trinational)	NMX-J-009/248/1-ANCE, Low-Voltage Fuses – Part 1: General Requirements (Trinational)

3 Units of Measurement

3.1 The values given in SI (metric) shall be normative. Any other values given shall be for information purposes only.

4 General

4.1 In Canada, general requirements applicable to this Standard are given in CSA C22.2 No. 0, General Requirements – Canadian Electrical Code, Part II.

5 Classification

5.1 Class CD Fuses are non-renewable and current-limiting with an interrupting rating of 200,000 A. Time-delay ratings are optional.

6 Characteristics

6.1 Voltage rating

- 6.1.1 For AC, the voltage rating shall be 600 V ac.
- 6.1.2 The DC voltage rating may be different from the AC rating.

6.2 Current rating

6.2.1 The current rating shall be 31 - 60 A.

6.3 Interrupting rating

- 6.3.1 For AC, the interrupting rating shall be 200,000 A.
- 6.3.2 For DC, the preferred ratings are 10,000, 20,000, 50,000, 100,000, 150,000, or 200,000 A.

6.4 Peak let-through current and clearing l²t characteristics

6.4.1 Maximum values of peak let-through current and clearing of tare given in Table 6.1.

Table 6.1 Table 6.1 Maximum Peak Let-through Current and Clearing I²t for Class CD fuses

	Between threshold and 50 kA		At 100 kA		At 200 kA	
Current rating I _n , A	Peak let- through current, A	l ² t, ampere- squared seconds	Peak let- through current, A	l ² t, ampere- squared seconds	Peak let- through current, A	l ² t, ampere- squared seconds
31 – 60	8,000	30,000	10,000	30,000	16,000	30,000

7 Construction

7.1 Fuse dimensions shall be as specified in Figure 7.1.